

HEAVY DUTY ROTARY TILLER



FIELDKING



FEATURES

Rotary Tiller (Rotavator) is better than conventional tillage equipment because it saves time, fuel, soil compaction & wear and tear of the tractor as it accomplishes better pulverization in the shortest time. It leaves the worked soil perfectly levelled. Roots & residue of previous crops are chopped into pieces and thoroughly mixed into soil to form organic manure. No need for multiple operations of cultivator, disc harrow and leveller. Puddling in wet fields is done smoothly, quickly & efficiently. Sealed bearings prevent moisture/mud entry, resulting in longer bearing protection.

SPECIFICATIONS

Model	FRT125	FRT150	FRT175	FRT200	FRT225
Tillage width (cm)	125	150	175	200	225
Gear box	Single Speed (540 RPM)				
Side transmission	Gear Drive				
Shape of blades	L				
No of flanges	5/5/8	6/6/10	7/7/12	8/8/14	9/9/16
No of blades	30/30/48	36/36/60	42/42/72	48/48/84	54/54/96
Gearbox overload protection	Shear Bolt/Slip Clutch				
Weight (kg)	420	450	480	510	540
Tractor power (hp/kw)	35-40/26-30	40-45/30-33	45-50/33-37	50-60/37-44	60-70/44-52

