

HP/kW
95-118/71-88

New Holland TS6 Series

- With roots tracing back to some of the oldest New Hollands, this reliable, simple series is famous for its rock-solid construction and simple maintenance.
- Being a true all-rounder this tractor can handle anything you throw at it, be it loading or mowing grass, or anything in between.
- The series have strong, rugged yet simple engines, making the tractor a reliable powerhouse.
- The TS6 series tractors combine legendary New Holland rugged drive lines with a host of choices to match your specific operational needs.
- The series offer a fully synchronised transmission system with easy forward/reverse shifting.
- The TS6 series tractors are available with a wider selection of transmissions 8x8 Mechanical Shuttle, 8x8 Hydraulic Shuttle and 16x8 Dual power Hydraulic Shuttle.
- With a high crop clearance of up to 30cm at the drawbar the TS6.120 maneuvers easily down rows of speciality crops.
- The spacious flat deck platform provides ultimate comfort having a wide, open work station, padded and contoured mechanical-suspension seat with armrests, adjustable tilt steering wheel, and great overall visibility are the standard equipment. In short an easy and comfortable tractor to operate



SPECIFICATIONS

		TS6.110	TS6.120	TS6.140
Engine				
Engine Type		4 Cylinder		6 Cylinder
Make / model		NH FPT / NEF		
Displacement	(Litres)	4.5		6.7
Aspiration		Turbo Intercooled		
Emissions certification		Tier 3		
Rated power	(kW/hp)	82/110	88/118	104/139
Power	(kW/hp)	71/95	74/99	88/118
Maximum torque @1250rpm	(Nm)	510	515	625
Forward Speed				
30kph version (18.4R38)	(kph)		31.7	
40kph version (18.4R38)	(kph)		40.5	
Transmission				
8x8 synchronized shuttle -left hand shuttle			Standard	
8x8 hydraulic shuttle -left hand shuttle			Optional	
16x8 Hi-Low hydraulic shuttle -left hand shuttle			Optional	
Creeper option (all transmissions)			Optional	
PTO (fully independent wet clutch)				
Speed Standard/Optional		540/540 -1000		540-1000
3 Point Hitch				
Category			II	
Draft sensing			Top link	
Max lift capacity – no assist ram	(kg)		2410	
Max lift capacity – 1 assist ram	(kg)		3639	
Max lift capacity – 2 assist ram s	(kg)		4647	
Hydraulics				
Standard flow pump	(Litre/min)		49	
“High Flow” pump	(Litre/min)		83	
Steering				
Steering pump flow	(Litre/min)		34	
Wheelbase				
2wd		2571		2631
4wd		2520		2627
Axles				
Front 2wd adjustable tread width	(mm)		1422-2032	
Front 4wd adjustable tread width	(mm)		1626-2032	
Flange axle – rear adjustable tread width	(mm)		1626-2032	
Optional bar axle - rear adjustable tread width	(mm)		1575-2337	
Front axle turn angle 2wd/4wd	(°)		55	
Weight				
Minimum shipping weight:				
2wd ROPS/CAB	(kg)	3630/3950	3670/4030	4110/4430
4wd ROPS/CAB	(kg)	3920/4240	4000/4320	4400/4720
Dimensions				
Overall length:				
2wd/4wd	(mm)	4115/4216		4191/4293
Height to top of ROPS	(mm)		2959	
Height to top of CAB	(mm)		2816	
Height to top of exhaust	(mm)	2700		2940
Key Configurations				
2wd ROPS			Optional	
2wd CAB			Optional	
4wd ROPS			Standard	
4wd CAB			Optional	
High Clearance (4wd only)		N/A	Optional	N/A